



## TARKETT ADHESIVE GUIDE

Floorings	Best choice	Good choice	Glueing method		Consumption
			Absorbent substrate	Non-absorbent substrate	
iQ Granit, iQ Eminent, iQ Megalit, iQ Optima, iQ Natural, Primo Premium, Eclipse Premium, Standard Plus	Floor Plus Extra	Floor Plus Extra	Floor Plus Extra	Floor Plus Extra	4-6 m <sup>2</sup> /litre
<b>Wall coverings</b>					
Wallgard	M1000 Eco Floor Plus		Wet bonding / late bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Acoustics</b>					
iQ Granit Acoustic, iQ Optima Acoustic, iQ Granit Ergofloor	Extra M1000 Eco		Late wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Step safety</b>					
Granit Multisafe Optima Multisafe Granit Safe. T	Floor Plus M1000 Eco		Late wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Conductive</b>					
iQ Granit SD, iQ Toro SC	-		-	-	-
<b>Wet room</b>	<b>Floor</b>	<b>Wall</b>			
iQ Optima 1,5 mm, Aquarelle floor & wall	Floor Plus M1000 Eco	Floor Plus M1000 Eco	Wet bonding / late wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Waterproofing - wall and floor</b>	<b>Floor</b>	<b>Wall</b>			
TarkoDry	Floor Plus M1000 Eco Extra	Floor Plus M1000 Eco Extra	Wet bonding / late wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Linoleum</b>					
<b>Floorings</b>					
Linoleum x <sup>2</sup> with jute backing	Floor Plus	Floor Plus	Wet bonding	Not recommended	4 m <sup>2</sup> /litre



Floorings	Best choice	Good choice	Glueing method		Consumption
			Absorbent substrate	Non-absorbent substrate	
<b>Linoleum Acoustics</b>					
Linoleum x <sup>2</sup> Acoustic Polyurethane backed	Floor Plus	Floor Plus	Late wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Step safety</b>					
Sicuro x <sup>2</sup> R10 with jute backing	Floor Plus	-	-	Not recommended	4 m <sup>2</sup> /litre
<b>Conductive</b>					
Sicuro x <sup>2</sup> SD with jute backing	Floor Plus	-	-	Not recommended	4 m <sup>2</sup> /litre
<b>Underlayer</b>					
Elafono, cork	Floor Plus M1000 Eco		Wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>LVT vinyl tiles</b>					
iD Inspiration	Floor Plus		Wet bonding	Not recommended	2-3 m <sup>2</sup> /litre
iD Inspiration	Slim (high traffic areas, special applications)		Wet bonding	Wet bonding	2-3 m <sup>2</sup> /litre
<b>PVC-free floor</b>					
iQ One	M1000 Eco Extra	Floor Plus	Wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
<b>Heterogeneous vinyl floor</b>					
Acczent Compact, Acczent Acoustic	Extra	Floor Plus	Wet bonding	Tack glueing	4-6 m <sup>2</sup> /litre
<b>Wood floor</b>					
	Flex Flexsilan	MS Silex	Wet bonding	Wet bonding	1-2 m <sup>2</sup> /litre
<b>Textile Desso</b>					
Butyl backing	Pro Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre
	Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre



Floorings	Best choice	Good choice	Glueing method		Consumption
			Absorbent substrate	Non-absorbent substrate	
Ecobase backing	Pro Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre
	Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre
	Pro Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre
Soundmaster backing	Grip		Tack glueing	Tack glueing	6-12 m <sup>2</sup> /litre
<b>Tarkett constructions</b>					
Underlayer Elafono (cork)	Floor Plus M1000 Eco		Wet bonding	Not recommended	4-6 m <sup>2</sup> /litre
Tarkolay + iQ Produkter (excl. iQ One)	-	-	-	-	-
Tarkolay + Acczent, Tapiflex	-	-	-	-	-